

Authorized Sales & Service
J. HERBERT CORPORATION
 Call 1-800-255-0588
 407-846-0588 Fax: 846-1066
 info@jherbertcorp.com
 Visit us online:
 www.jherbertcorp.com

HEAVY DUTY Cable Reels 20-70 ft., retraction weight 4 lbs.

Weather- and dust-resistant enclosure meets NEMA 4 rating for outdoor use. Rugged Steel construction in a compact design. Quick change spring motor, long life containerized guide. Steel flange and stand, bronze ball bearings. Ratchet lock may be disengaged for constant tension, direct spring drive, maximum lifting speed of 150 f.p.m. Retraction weight: 4 lbs. 600V rated SOW cable. Collector ring rating is 35A for AWG sizes 10-16. Collector ring rating is 75A for AWG sizes 6 and 8. Guide arm can be adjusted in 5° increments. Ball stops are available on page 197.



Heavy Duty Cable Reels

WIRE GAUGE	COND.	AMPS ¹	CABLE LENGTH (PART NO. / LENGTH)						WITHOUT CABLE	
			20'	30'	40'	50'	60'	70'	PART NO.	CABLE RANGE
16 AWG	3	10A	—	—	—	—	—	92531N	10511303GOL000	up to 70'
	4	8A	—	—	—	—	—	92541N	10511304GOL000	up to 70'
	6	8A	—	—	—	—	—	92561N	10511306GOL000	up to 70'
	8	7A	—	—	—	—	—	92581N	10511308GOL000	up to 70'
	10	5A	—	—	—	—	92501AN	10511310GOL000	up to 50'	
14 AWG	12	5A	—	—	—	—	92511AN	10511312GOL000	up to 50'	
	3	15A	—	—	—	—	—	92532N	10511303GOL000	up to 70'
	4	12A	—	—	—	—	—	92542N	10511304GOL000	up to 70'
	6	12A	—	—	—	—	92562AN	10511306GOL000	up to 50'	
	6	12A	—	—	—	—	—	92562BN	10512306GOL000	50-70'
	8	10A	—	—	—	—	—	92582N	10512308GOL000	up to 60'
	10	7A	—	—	—	—	—	92502N	10512310GOL000	up to 50'
12 AWG	12	7A	92512AN	—	—	—	—	—	10511312GOL000	up to 30'
	12	7A	—	—	92512BN	—	—	—	10512312GOL000	30-40'
	3	20A	—	—	—	—	—	92533N	10511303GOL000	up to 70'
10 AWG	4	16A	—	—	—	—	—	92543N	10511304GOL000	up to 60'
	6	14A	—	—	—	—	—	92663	10512306GOL000	up to 60'
	8	14A	—	—	—	—	—	92583N	10512308GOL000	up to 50'
8 AWG	3	25A	—	—	—	—	—	92534N	10512303GOL000	up to 70'
	4	20A	—	—	—	—	—	92544AN	10512304GOL000	up to 70'
	6	20A	—	—	—	—	—	92564N	10513306GOL000	up to 50'
6 AWG	8	14A	—	92584N	—	—	—	—	10512308GOL000	up to 30'
	2	35A	—	—	—	—	—	—	1051140200L000	up to 40'
	2	35A	—	—	—	—	—	—	1051240200L000	40-50'
	3	35A	—	92535AN	—	—	—	—	10511403GOL000	up to 30'
4	3	35A	—	—	—	—	—	—	10512403GOL000	30-50'
	4	28A	—	92545AN	—	—	—	—	10511404GOL000	up to 20'
	4	28A	—	—	—	92545AN	—	—	10513404GOL000	30-40'
	2	45A	—	92526AN	—	—	—	—	1051240200L000	up to 40'
3	2	45A	—	—	—	—	—	—	1051340200L000	40-50'
	3	45A	—	92536N	—	—	—	—	10513403GOL000	up to 30'
	4	36A	92546N	—	—	—	—	—	10513404GOL000	up to 30'

¹ THE CORD REEL AMPERAGE RATINGS LISTED ARE DE-RATED FIGURES. THEY ARE BASED ON THE CABLE BEING SPOOLED AND RUN AT FULL LOAD. THE RATINGS SUPPLIED BY CABLE MANUFACTURERS ARE WITH THE CABLE FULLY EXTENDED IN FREE AIR. FOR MORE COMPLETE DATA OR SPECIFIC DETAILS, PLEASE REFER TO THE NATIONAL ELECTRICAL CODE.

UL SEI MOST WOODHEAD PRODUCTS HAVE U.L. AND/OR CSA APPROVALS. FOR A LISTING OF APPROVALS BY PART NUMBER, SEE PAGES 262-269.

HEAVY DUTY Cable Reels 40-160 ft., retraction weight 7 lbs.

Rugged steel construction in a compact design. Weather- and dust-resistant enclosure meets NEMA 4 rating for outdoor use. Quick change spring motor, long-life containerized main-spring, declutching drive hub, lifetime lubrication. Steel flange stand, bronze ball bearings. Ratchet lock can be disengaged for constant tension. Direct drive with lifting speed of 150 f.p.m. Retraction weight: 7 lbs. 600V rated SOW cable. Collector ring rating is 35A for AWG sizes 10-16. Collector ring rating is 75A for AWG sizes 6 and 8. Ball stops are available on page 197.



Heavy Duty Cable Reels

WIRE GAUGE	COND.	AMPS ¹	CABLE LENGTH (PART NO. / LENGTH)			WITHOUT CABLE		
			40-65'	80-110'	115-160'	PART NO.	CABLE RANGE	
16 AWG	3	9A	—	—	92631 / 115'	114310303GOL ²	up to 115'	
	4	7A	—	—	92641 / 115'	114310304GOL ²	up to 115'	
	6	7A	—	92661 / 100'	—	114310306G1L	up to 100'	
	6	7A	—	—	92761 / 150'	116505306G1L	100-150'	
	8	6A	—	92681 / 95'	—	114310308G1L	up to 95'	
	8	6A	—	—	92781 / 150'	116505308G1L	95-150'	
14 AWG	3	13A	—	92632 / 110'	—	114310303G1L	up to 110'	
	3	13A	—	—	92732 / 160'	116505303G1L	110-160'	
	4	11A	—	92642 / 110'	—	114310304G1L	up to 110'	
	4	11A	—	—	92742 / 160'	116505304G1L	110-160'	
	6	11A	—	—	92762 / 115'	116505306G2L	up to 115'	
	8	8A	—	92782 / 90'	—	116505308G2L	up to 90'	
	10	7A	92702 / 60'	—	—	116505310G3L	up to 60'	
	12	6A	92712 / 60'	—	—	116505312G3L	up to 60'	
	12 AWG	3	18A	—	92633 / 95'	—	114310303G1L	up to 95'
		3	18A	—	—	92733 / 160'	116505303G1L	95-160'
4		14A	—	92643 / 80'	—	114310304G2L	up to 80'	
4		14A	—	—	92743 / 140'	116505304G2L	80-140'	
6		14A	—	92763 / 95'	—	116505306G2L	up to 95'	
8		12A	92783 / 60'	—	—	116505308G3L	up to 60'	
10 AWG	3	22A	—	—	92734 / 130'	116505303G2L	up to 130'	
	4	16A	—	—	92744 / 120'	116505304G2L	up to 120'	
	6	14A	—	92764 / 85'	—	116505306G3L	up to 85'	
	8	14A	92784 / 50'	—	—	116505308G4L	up to 50'	
8 AWG	2	40A	92625 / 60'	—	—	114310402J3L	up to 60'	
	2	40A	—	92725 / 95'	—	116505402J3L	60-95'	
	3	35A	—	92735 / 85'	—	116505403G4L	up to 85'	
	4	32A	92745 / 60'	—	—	116505404G5L	up to 60'	
6 AWG	2	55A	92726 / 65'	—	—	116505402J4L	up to 65'	
	3	45A	92736 / 50'	—	—	116505403G5L	up to 50'	
	4	44A	92746 / 40'	—	—	116505404G6L	up to 40'	

¹ THE CORD REEL AMPERAGE RATINGS LISTED ARE DE-RATED FIGURES. THEY ARE BASED ON THE CABLE BEING SPOOLED AND RUN AT FULL LOAD. THE RATINGS SUPPLIED BY CABLE MANUFACTURERS ARE WITH THE CABLE FULLY EXTENDED IN FREE AIR. FOR MORE COMPLETE DATA OR SPECIFIC DETAILS, PLEASE REFER TO THE NATIONAL ELECTRICAL CODE.

² CAN BE USED FOR RECOVERY APPLICATIONS. NOTE: IT IS STRONGLY RECOMMENDED THAT A SECONDARY SAFETY CABLE OR CHAIN BE ATTACHED TO ALL REELS MOUNTED OVERHEAD TO PREVENT THE POSSIBILITY OF REELS ACCIDENTALLY FALLING.

UL SEI MOST WOODHEAD PRODUCTS HAVE U.L. AND/OR CSA APPROVALS. FOR A LISTING OF APPROVALS BY PART NUMBER, SEE PAGES 262-269.

CALL YOUR SALES REP TODAY!