

S35 TILTERS

KEY FEATURES

- Lubricated-for-life composite bearings on all pivot points
- Solid steel platform with stiffener bars
- Turned, ground, polished and hard-chromed axle pins
- Direct thrust cylinders
- Chrome plated cylinder rods
- Double-wire braided hydraulic hoses
- Maintenance (safety) devices
- Polyethylene fluid reservoir
- Factory tested to 110% capacity
- Internally mounted and pre-wired power unit with UL listed components
- Built and designed in accordance with ANSI MH29.2
- Safety labels comply with ANSI Z535
- One year warranty

BENEFITS

- Maintenance-free bearings, no greasing required
- Minimal platform deflection
- Extended bearing life
- Provides the lowest collapsed height
- Corrosion resistance adds to life of cylinder
- Extended hose life for added safety
- Easy servicing of hydraulic components
- Easy inspection for fluid level, condensation and pollutants
- Exacting standards means it works the first time, every time
- Ready-to-operate with zero plumbing and minimal wiring components
- Designed to meet or exceed all industry standards
- Adds to employee's safety as the lift meets all industry standards for labeling
- Built to last with the best warranty in the industry

POWER SUPPLY The electric motor is internally mounted. It is available in either 1 1/2 hp three-phase or 3/4 hp single-phase, with 24V AC control voltage.

CUSTOM DESIGNS

A number of "customized" engineering plans are already on file for the STE Series. Additionally, Autoquip offers computerized engineering services for development of "one-of-a-kind" ergonomic tilter applications.

Authorized Sales & Service

J. HERBERT CORPORATION

Call 1-800-255-0588

407-846-0588 Fax: 846-1066

info@jherbertcorp.com

Visit us online:

www.jherbertcorp.com

SPECIFICATIONS: 30° to 45° Travel; Capacities 2,500 to 6,000 lbs.

Travel (degrees)	Capacity (lbs.)	Series 35 Model No.	Lowered Height (in.)	Raising or Lowering Time (sec.)	Standard Platform (in.)	Base Size (in.)	Electric Motor (hp)	No. of Cyl.	Shipping Weight (lbs.)
30	2,500	STE 30-25-4	8	5	44 x 44	24 x 41	1.5	1	500
45	2,500	STE 45-25-4	8	8	44 x 44	24 x 41	1.5	1	525
30	2,500	STE 30-25-5	8	5	50 x 50	24 x 41	1.5	1	600
45	2,500	STE 45-25-5	8	8	50 x 50	24 x 41	1.5	1	625
30	4,000	STE 30-40-4	8	5	44 x 44	24 x 41	1.5	1	525
45	4,000	STE 45-40-4	8	8	44 x 44	24 x 41	1.5	1	550
30	4,000	STE 30-40-5	8	5	50 x 50	24 x 41	1.5	1	625
45	4,000	STE 45-40-5	8	8	50 x 50	24 x 41	1.5	1	650
30	6,000	STE 30-60-4	8	5	44 x 44	24 x 41	1.5	1	550
45	6,000	STE 45-60-4	8	8	44 x 44	24 x 41	1.5	1	575
30	6,000	STE 30-60-5	8	5	50 x 50	24 x 41	1.5	1	650
45	6,000	STE 45-60-5	8	8	50 x 50	24 x 41	1.5	1	675