

MANUAL TURNTABLES

KEY FEATURES

- 1/2" thick steel platform with radius corners
- Turned, ground, polished & hard-chromed kingpin
- Sealed double row ball bearing rollers
- Rigid base with mounting holes
- Extremely easy to turn
- Factory tested to 110% of capacity
- Safety labels comply with ANSI Z535
- One year warranty

BENEFITS

- Minimal deflection, great durability
- Extended bearing life
- Maintenance free bearings, no greasing required. Extremely easy to turn
- Simple to relocate
- Reduced work fatigue
- Exacting standards means it works the first time, every time
- Adds to employee's safety as the turntable meets industry standard for labeling
- Built to last with the best warranty in the industry

CUSTOM DESIGNS

A number of "customized" engineering plans are already on file for the SR Series. Additionally, Autoquip offers computerized engineering services for development of "one-of-a-kind" manual applications.



(Lift not included; sold separately.)

Authorized Sales & Service
J. HERBERT CORPORATION
 Call 1-800-255-0588
 407-846-0588 Fax: 846-1066
 info@jherbertcorp.com

Visit us online:
www.jherbertcorp.com

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Rectangular Manual Turntable

Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SR4-36-25	36 x 36	24 x 24	4	200
4,000	SR4-36-40	36 x 36	24 x 24	4	200
6,000	SR4-36-60	36 x 36	24 x 24	4	200
2,500	SR4-42-25	42 x 42	24 x 24	4	275
4,000	SR4-42-40	42 x 42	24 x 24	4	275
6,000	SR4-42-60	42 x 42	24 x 24	4	275
2,500	SR4-4248-25	42 x 48	24 x 24	4	300
4,000	SR4-4248-40	42 x 48	24 x 24	4	300
6,000	SR4-4248-60	42 x 48	24 x 24	4	300
2,500	SR4-48-25	48 x 48	24 x 24	4	350
4,000	SR4-48-40	48 x 48	24 x 24	4	350
6,000	SR4-48-60	48 x 48	24 x 24	4	350

SPECIFICATIONS: 2,500 to 6,000 lb. capacity Round Manual Turntable

Capacity (lbs.)	Series 35 Model No.	Platform Size (in.)	Base Size (in.)	Total Height (in.)	Shipping Weight (lbs.)
2,500	SR4R-36-25	36	24 x 24	4	200
4,000	SR4R-36-40	36	24 x 24	4	200
6,000	SR4R-36-60	36	24 x 24	4	200
2,500	SR4R-42-25	42	24 x 24	4	275
4,000	SR4R-42-40	42	24 x 24	4	275
6,000	SR4R-42-60	42	24 x 24	4	275
2,500	SR4R-48-25	48	24 x 24	4	350
4,000	SR4R-48-40	48	24 x 24	4	350
6,000	SR4R-48-60	48	24 x 24	4	350