

# Accessories

## Series PTF Manual Trolleys for I-Beams

The Series PTF manual trolleys are used for suspending small air hoist from I-beams, railways, or jib booms. Model PTF-125 and PTF-250 are easily adjustable for different size beams. In addition, the frame is designed to protect the wheels from collisions with other trolleys and can be fitted with rubber bumpers for further protection. Dimensions are available in CAT1007 balancer catalog - Pg. 27.



Series PTF-125

Capacity lb (kg)	Min Curve Radius in (mm)	Part No.	Beam Width in (mm)	Wt lb (kg)
276 (125)	24 (600)	<b>PTF-125</b>	2.0 / 2.95 (50 / 75)	3.50 (1.60)
551 (250)	35 (900)	<b>PTF-250</b>	2.95 / 3.93 / 4.92 (75 / 100 / 125)	9.25 (4.20)



Series PTF-250


## Cleaner Set

This device reduces noise and exhausted oil from the hoist exhaust ports. It is available for the models listed.



Part No.	Use on Hoist Model	Wt lb (kg)
<b>LHP001343</b>	EHL-025TS, EHL-05TS, EHL-098TW, EHL-1TW	2.21 (1.0)
<b>LHP001388</b>	EHL-1TS, EHL-2TW	2.21 (1.0)
<b>LHP001389</b>	EHL-3TS, EHL-6TW	3.53 (1.6)

## Overload Protector



Use on Hoist Model:	Part No.	Wt lb (kg)
EHL-05TS	<b>OP-05TS</b>	4.41 (2.0)
EHL-1TW	<b>OP-1TW</b>	4.85 (2.2)
EHL-1TS	<b>OP-1TS</b>	13.67 (6.2)
EHL-2TW	<b>OP-2TW</b>	13.67 (6.2)
EHL-3TS	<b>OP-3TS</b>	48.50 (22.0)
EHL-6TW	<b>OP-6TW</b>	48.50 (22.0)

## Stainless Steel Load Chain

Due to the lower load capacity of stainless steel chain, the nominal load capacity of the EHL-1TS and EHL-2TW would be reduced 20% using this chain instead of the standard chain. Not available for 3 and 6 tonne hoists. Contact the Factory for part numbers and prices.

## Chain Buckets

Larger buckets can be used when replacing the factory chain with a longer chain.

Part No.	(6 m)	(10 m)	(12 m)	(20 m)
<b>AT-60K and AT-125K</b>	Std	Contact Factory	Opt	Opt
<b>EHL-025TS and EHL-05TS</b>	Std	Contact Factory	Opt	Opt
<b>EHL-098TW and EHL-1TW</b>	Std	Contact Factory	Opt	Opt
<b>EHL-1TW and EHL-2TW</b>	Std	Contact Factory	Opt	Opt
<b>EHL-3TS and EHL-6TW</b>	Std	Optional	Contact Fact.	Contact Fact.