



Authorized Sales & Service
J. HERBERT CORPORATION
 Call 1-800-255-0588
 407-846-0588 Fax: 846-1066
 info@jherbertcorp.com
 Visit us online:
 www.jherbertcorp.com

Coffing AMT

Air Motor Trolley Air Motor Trolley

Coffing Model AMT is designed to operate with Coffing CAH air chain hoists for faster positioning of the hoist in a variety of lifting applications. Air trolleys provide power in locations where electricity are not a viable option.

Additional features and benefits include:

- Variable speeds up to 50 FPM 1/4 to 1 ton and up to 60 FPM 2 and 3 ton.
- 8-Vane motor provides high torque, smooth starting, and excellent control.
- Steel frame side plates extend beyond wheels for end stop contact. Sideplates have tapped holes suitable for bracket attachments such as festooning arms or safety lugs.
- Forged, heat-treated steel, with dual tread for use on Standard or wide flange beams. Wheel bearings are sealed, life-time-lubricated precision ball bearings.
- Pendant throttle control provides precise, controlled spotting and efficient load handling.
- Options - Spark resistant models. Rated loads 3/8 - 2 ton. For areas where spark protection is required in hazardous environments. Same features apply to these models with the addition of spark resistant bronze wheels.
- Air Supply Consumption: 50 SCFM; Pressure: 90 PSI.
- Lifetime warranty



The above picture may not be an exact representation of the product

Product image above may show optional features and accessories not included on standard models. Consult with a sales rep or with the product catalog for more information.

716.689.5400 • 800.888.0985 • Fax: 716.689.5644 • www.cmworks.com