

Series AT Chain Air Hoist



The compact, light-weight AT-60K and AT-125K hoists combine the high speeds of wire rope hoists (up to 77 ft./minute) with the high durability of chain hoists. These hoists are ready for operation right out of the box; just connect lubricated air. Can be mounted on air trolley or manual trolley - by request.

- Conical brake and rotary vane motor design
- Pendant control for precise variable lifting and lowering speed
- Low headroom - approximately 14 inches (356mm)
- Chain size: 4 x 12 mm, 11 links per 132 mm section of chain
- **Lift Height:** 9.8 feet (3 meters). Chain extension available.

Rated Load lb (kg)	Part No.	Air Pressure		Lifting Speed		Air Consumption		Air Inlet	Wt	
		bar	PSI	m/min	ft/min	m3	cfm	in.	lb	(kg)
132 (60)	AT-60K	4	(58)	16.5	(54)	0.52	(18)	0.375	27	(12.3)
		5	(72)	20.0	(66)	0.67	(23)			
		6	(87)	23.5	(77)	0.85	(30)			
275 (125)	AT-125K	4	(58)	10.0	(33)	0.55	(19)	0.375	28	(12.5)
		5	(72)	12.0	(39)	0.71	(25)			
		6	(87)	14.5	(47)	0.9	(31)			

Optional Speed Control: Standard control is shown at the left. To order optional control with red emergency stop button - shown at the right - add "-5" to the part number.

