

# EW-X Series "ECO" Balancers



EWS-5X

The Series "X" balancers are the "eco-friendly" balancers. They are the ultimate solution when particulates from the standard exterior balancer finish might contaminate food or sensitive assemblies. The basic features of the EW style are on Pg. 9; the EWS on Pg. 14; the EWF on Pg. 10. The specific features of the "X" version are as follows:

- Buffed and barrel-polished casing and cover
- Synthetic food-grade grease (H1 grade) on the spring
- Stainless steel lower hook, plug, rivet, bolts, and screws
- Zinc plated upper hook and pins

#### Rope Types:

- EW-3 to EWS-7: White Nylon, 3 mm diameter. EWF-9 to EWF-15: Black Nylon, 4 mm diameter
- EWF-22 to EWF-120: Stainless Steel, 4.8 mm diameter



EWF-22X

Max. Capacity lb (kg)	Cable Travel ft (m)	Part No.	Wt lb (kg)
2.2 to 6.6 (1.0 to 3.0)	4.27 (1.3)	<b>EW-3X</b>	3.1 (1.4)
3.3 to 6.6 (1.5 to 3.0)	4.27 (1.3)	<b>EWS-3X</b>	4.2 (1.9)
5.5 to 11.0 (2.5 to 5.0)	4.27 (1.3)	<b>EW-5X</b>	3.3 (1.5)
6.6 to 11.0 (3.0 to 5.0)	4.27 (1.3)	<b>EWS-5X</b>	4.6 (2.1)
11.0 to 15.4 (5.0 to 7.0)	4.27 (1.3)	<b>EWS-7X</b>	4.6 (2.1)
9.9 to 19.8 (4.5 to 9.0)	4.27 (1.3)	<b>EWF-9X</b>	7.5 (3.4)
19.8 to 33.1 (9.5 to 15.0)	4.93 (1.5)	<b>EWF-15X</b>	8.4 (3.8)
33.1 to 48.5 (15 to 22)	4.93 (1.5)	<b>EWF-22X</b>	16.1 (7.3)
48.5 to 66.1 (22 to 30)	4.93 (1.5)	<b>EWF-30X</b>	17.0 (7.7)
66.1 to 88.2 (30 to 40)	4.93 (1.5)	<b>EWF-40X</b>	21.4 (9.7)
88.2 to 110.2 (40 to 50)	4.93 (1.5)	<b>EWF-50X</b>	11.7 (10.1)
110.2 to 132.3 (50 to 60)	4.93 (1.5)	<b>EWF-60X</b>	24.5 (11.1)
132.3 to 154.3 (60 to 70)	4.93 (1.5)	<b>EWF-70X</b>	25.1 (11.4)
154.3 to 198.4 (70 to 90)	6.56 (2.0)	<b>EWF-90X</b>	48.5 (22.0)
198.4 to 231.5 (90 to 105)	6.56 (2.0)	<b>EWF-105X</b>	53.0 (24.0)
231.5 to 264.5 (105 to 120)	6.56 (2.0)	<b>EWF-120X</b>	61.7 (28.0)

For dimensional drawings, see Pg. 22