

# Series ATC Chain Air Hoist



The Series ATC Air Hoist features direct-controlled operation and is ready to use. Just connect lubricated air supply. Provides precise variable lifting and lowering speed. Can be mounted on air trolley or manual trolley - by request.

- Manipulator-style pendant control for precise variable lifting and lowering speed
- Air Inlet is 3/8" NPT
- Chain size: 4 x 12 mm, 11 links per 132 mm section of chain
- **Lift Height:** 6.65 ft. (2 meters)

Rated Load lb (kg)	Part No.	Air Pressure		Lifting Speed		Air Consumption		Wt lb (kg)
		bar	PSI	m/min	FT/min	m3	cfm	
132 (60)	ATC-60K	4	(58.0)	14.0	(45.9)	0.52	(18.0)	31.5 (14.3)
		5	(72.5)	17.0	(55.8)	0.67	(23.0)	
		6	(87.0)	20.0	(65.6)	0.85	(30.0)	
275 (125)	ATC-125K	4	(58.0)	6.5	(21.3)	0.55	(19.0)	32.0 (14.5)
		5	(72.5)	10.5	(34.49)	0.71	(25.0)	
		6	(87.0)	12.0	(39.4)	0.9	(31.0)	

**Optional Speed Control:** Standard control is shown at the left. To order optional control with red emergency stop button - shown at the right - add "-5" to the part number.

