

# Wide Applications

Authorized Sales & Service  
**J. HERBERT CORPORATION**  
 Call 1-800-255-0588  
 407-846-0588 Fax: 846-1066  
 info@jherbertcorp.com  
 Visit us online:  
 www.jherbertcorp.com



**The Caldwell Group** • 800-628-4263 • www.caldwellinc.com 2014-2016 Master Catalog

## Model D - Twin Crossarms with 4 Pads - Standard Duty

For lifting wide or thin material. The crossarms make the load easier to balance.

**QUICKSHIP PROGRAM**

### PRODUCT FEATURES:

- Ball mounted vacuum pads.
- Brass fittings.
- Push lock hose (designed for 250 psi).
- Slide valves allow for manual isolation of vacuum pads.
- Muffler/filter is spin on type for easy change out.



Model DE6S6-6-D3 shown.

Univac® 250 for capacities less than 1,240 pounds.



Model DE16V8-6-D3 shown

Univac® 250 for capacities of 1,240 to 2400 pounds.

### SPECIFICATIONS

Add FEET to blank Model Number box to complete code.  
 Example: 5' load beam - DA16V8-**LENGTH**-D3

Rated Capacity (lbs.)	Base Wt. @ 5' (lbs.)	Model Number	Power-Pac	Flared Diameter (in.)	Load Beam Length (ft.)		
					5	6	8
<b>Electric</b>							
<b>With 3' Crossarm Beams</b>							
680	290	DE6S6 <input type="checkbox"/> D3	UNIVAC-250	7-1/4	5	6	8
1240	310	DE12S8 <input type="checkbox"/> D3	UNIVAC-250	9-5/8	5	6	8
1600	350	DE16V8 <input type="checkbox"/> D3	UNIVAC-250	10-5/8	5	6	8
2400	365	DE24V10 <input type="checkbox"/> D3	UNIVAC-250	12-1/4	5	6	8
<b>With 4' Crossarm Beams</b>							
680	300	DE6S6 <input type="checkbox"/> D4	UNIVAC-250	7-1/4	5	6	8
1240	315	DE12S8 <input type="checkbox"/> D4	UNIVAC-250	9-5/8	5	6	8
1600	360	DE16V8 <input type="checkbox"/> D4	UNIVAC-250	10-5/8	5	6	8
2400	375	DE24V10 <input type="checkbox"/> D4	UNIVAC-250	12-1/4	5	6	8
<b>Shop Air - Venturi</b>							
<b>With 3' Crossarm Beams</b>							
680	315	DA6S6 <input type="checkbox"/> D3	V-40	7-1/4	5	6	8
1240	315	DA12S8 <input type="checkbox"/> D3	V-40	9-5/8	5	6	8
1600	320	DA16V8 <input type="checkbox"/> D3	V-40	10-5/8	5	6	8
2400	335	DA24V10 <input type="checkbox"/> D3	V-40	12-1/4	5	6	8
<b>With 4' Crossarm Beams</b>							
680	325	DA6S6 <input type="checkbox"/> D4	V-40	7-1/4	5	6	8
1240	325	DA12S8 <input type="checkbox"/> D4	V-40	9-5/8	5	6	8
1600	330	DA16V8 <input type="checkbox"/> D4	V-40	10-5/8	5	6	8
2400	345	DA24V10 <input type="checkbox"/> D4	V-40	12-1/4	5	6	8

Other sizes available, consult factory.